

# Conveyor Accessories

## Portable Castered Support



Portable Castered Support allows straight sections of gravity skatewheel or 1-3/8 in. dia. roller conveyor to be easily moved.

Support Width				Height to Top of Conveyor	Weight (Lbs.)
12"	15"	18"	24"		
PCS-12-28	PCS-15-28	PCS-18-28	PCS-24-28	18"-28"	53
PCS-12-40	PCS-15-40	PCS-18-40	PCS-24-40	24"-40"	55
PCS-12-52	PCS-15-52	PCS-18-52	PCS-24-52	30"-52"	57
PCS-12-72	PCS-15-72	PCS-18-72	PCS-24-72	40"-72"	62

NOTE: Supplied with 3 in. dia. Hard Rubber stem type brake caster.

All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.



## Portable Castered Curve Support



Portable Castered Curve Support allows curved sections of gravity skatewheel or 1-3/8 in. dia. roller curves to be easily moved. Floor locks can be supplied—optional, see Page 167.

Support Width				Height to Top of Conveyor	Weight (Lbs.)
12"	15"	18"	24"		
PCCS-12-28	PCCS-15-28	PCCS-18-28	PCCS-24-28	18"-28"	69
PCCS-12-40	PCCS-15-40	PCCS-18-40	PCCS-24-40	24"-40"	71
PCCS-12-52	PCCS-15-52	PCCS-18-52	PCCS-24-52	30"-52"	73
PCCS-12-72	PCCS-15-72	PCCS-18-72	PCCS-24-72	40"-72"	78

NOTE: Supplied with 3 in. dia. Hard Rubber stem type brake caster.

All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.

## Tripod Stand



Adjustable Tripod Stands are used with straight or curved sections of gravity skatewheel and 1-3/8 in. dia. roller conveyor. Optional leg angles can be supplied to fasten stand to floor.

- 4 widths
- Portable applications
- Easily adjusted

**CAPACITY DATA:**  
350 lbs. with 180 in./lbs. of torque on locking screw. (No Shock Loading).

All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.

Model No.	Width	Height (Top of Roller/Wheel)		Weight (Lbs.)
		Min.	Max.	
TS-12-18	12"	12"	18"	5-1/2
TS-12-30		18"	30"	8-1/2
TS-12-40		24"	40"	10-1/2
TS-12-52		30"	52"	13-1/2
TS-12-72		40"	72"	19-1/2
TS-12-110		60"	110"	23-1/2
TS-15-18	15"	12"	18"	6
TS-15-30		18"	30"	9
TS-15-40		24"	40"	11
TS-15-52		30"	52"	14
TS-15-72		40"	72"	20
TS-15-110		60"	110"	24
TS-18-18	18"	12"	18"	6-1/2
TS-18-30		18"	30"	9-1/2
TS-18-40		24"	40"	11-1/2
TS-18-52		30"	52"	14-1/2
TS-18-72		40"	72"	20-1/2
TS-18-110		60"	110"	24-1/2
TS-24-18	24"	12"	18"	7
TS-24-30		18"	30"	10
TS-24-40		24"	40"	12
TS-24-52		30"	52"	15
TS-24-72		40"	72"	21
TS-24-110		60"	110"	25

CONVEYOR ACCESSORIES

## Roller Stand



Adjustable Roller Stands are made of heavy gauge pipe with a 1.9 galvanized, ball bearing roller mounted on top. They are used for feeding work to a punch press, saw, drill press, brake press, or anywhere some extra support is required.

- 3 widths
- Portable applications
- Easily adjusted

MODEL NO.	WIDTH BR	HEIGHT		Weight (Lbs.)
		MIN.	MAX	
RTS-13-18	13"	12-3/8"	18"	9
RTS-13-30		18-3/8"	30"	12
RTS-13-40		24-3/8"	40"	14
RTS-13-18	17"	12-3/8"	18"	10
RTS-13-30		18-3/8"	30"	13
RTS-13-40		24-3/8"	40"	15
RTS-13-18	21"	12-3/8"	18"	12
RTS-13-30		18-3/8"	30"	15
RTS-13-40		24-3/8"	40"	17

All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.