



STANDARD
F93 SET HIGH



STRAIGHT SECTIONS

Model No.	B.F.	Roll Centers	10' Wt. Lbs.	5' Wt. Lbs.	Model No.	B.F.	Roll Centers	10' Wt. Lbs.	5' Wt. Lbs.	Model No.	B.F.	Roll Centers	10' Wt. Lbs.	5' Wt. Lbs.
1416-13-1.5	13	1.5	201	101	1416-21-1.5	21	1.5	280	140	1416-31-1.5	31	1.5	377	189
1416-15-1.5	15	1.5	220	110	1416-23-1.5	23	1.5	299	150	1416-33-1.5	33	1.5	397	199
1416-17-1.5	17	1.5	241	120	1416-25-1.5	25	1.5	318	160	1416-37-1.5	37	1.5	436	218
1416-19-1.5	19	1.5	261	130	1416-27-1.5	27	1.5	343	169	1416-39-1.5	39	1.5	456	227

STANDARD SPECIFICATIONS

Rollers: 1.375" dia., 16 ga. wall tubes with 7/16" hex cold rolled steel axles, spring retained. Standard A03 bearings are light oil lubricated. 290 lbs. roller capacity.

Frames: F93 set high 3" x 1-1/2" x 3/16" formed steel angles with bolted 1-1/8" x 1/8" angle crossies.

Widths: Standard widths are listed in table. Also available from 6" to 39" between frames.

Lengths: Standard 5' and 10'. Also available in 1" increments from 24" to 120".

Frame Capacity: 1300 lbs. evenly distributed live load per 10' section with supports on 10' centers; 3200 lbs. maximum evenly distributed live load with supports on 5' centers.

Roller Covers: Standard V98 : No roll cover.

Finish: Standard P94: Safety blue, Epoxy Powder Coat.

OPTIONAL COMPONENTS

FRAME	F93; F11, F29
ROLLER BEARING	A03;
ROLL COVER	V98; V40
FINISH	P94; P09, P11, P24, P45, P95, P99

*For descriptions of **OPTIONAL COMPONENTS** see pages 170-176.

HOW TO ORDER

1416 - BF - RC - LG - FRAME - RLBRG - ROLCV - FINISH

EXAMPLE: 1416-13-1.5-120-F93-A03-V98-P94

Our Vision: To be the finest conveyor distributor in the hearts and minds of the people we serve.



7-138 Anderson Avenue, Markham, L6E 1A4
 Phone: 905-471-0420, Fax: 905-471-6617
 Email: sales@mckessockconveyors.com
 www.mckessockconveyors.com

