



STRAIGHT SECTIONS				
Model No.	B.F.	Roll Centers	10' Wt. (Lbs.)	5' Wt. (Lbs.)
1011-10-1.125	10	1.125	165	83
1011-13-1.125	13	1.125	184	92
1011-16-1.125	16	1.125	204	102
1011-22-1.125	22	1.125	242	121

STANDARD SPECIFICATIONS	
<p>Rollers: 1.0" dia., 11 ga. wall tubes with 1/4" round cold rolled steel axles, spring retained. Standard A05 bearings are light oil lubricated. 50 lbs. roller capacity.</p> <p>Frames: Standard F99 set high 2-1/2" x 1" x 3/16" formed steel angles with bolted 1-1/8" x 1/8" angle crossies.</p> <p>Widths: Standard widths are listed in table. Also available from 6" to 22" between frames.</p> <p>Lengths: Standard 5' and 10'. Also available in 1" increments from 24" to 120".</p>	<p>Frame Capacity: 130 lbs. evenly distributed live load per 10' section with supports on 10' centers; 775 lbs. maximum evenly distributed live load with supports on 5' centers.</p> <p>Guard Rail: Standard G99: No guard rail.</p> <p>Roller Covers : Standard V98 : No roller cover</p> <p>Finish: Standard P94: Safety blue, Epoxy Powder Coat.</p>

OPTIONAL COMPONENTS	
FRAME	F99; F02, F03, F04, F05, F32
ROLLER BEARING	A05;
ROLL COVER	V98;
FINISH	P94; P09, P11, P24, P45, P95, P99

*For descriptions of OPTIONAL COMPONENTS see pages 169-175.

HOW TO ORDER
1011 - BF - RC - LG - FRAME - RLBGR - ROLCV - FINISH
EXAMPLE: 1011-10-1.125-120-F99-A05-V98-P94